

HONDA XR 190CT

AGRICULTURE - A TRUE WORKHORSE



KEY HIGHLIGHTS



Heavy duty carriers front & rear



13L (+3.9L reserve) fuel tank capacity



Strong, powerful and economic engine



Off-road tyres

The high performance 184cc engine has electronic fuel injection, ensuring it starts first time, every time. Honda XR190CT is the ultimate practical and durable choice for off-road conditions while carrying a load and the “big foot” side stands allow it to park on any terrain. Equipped with crossbar-design handlebar, lever guards, clutch lock and a wide comfortable seat, this motorcycle gets the job done in the agricultural sector or similar.



Support UN's Sustainable Development Goal 13

Take urgent action to combat climate change and its impacts

4-stroke engine technology is significantly cleaner than a 2-stroke engine due to a cleaner combustion and better fuel economy. Endorsed by UNEP.

13 CLIMATE ACTION



FREE DOWNLOAD CENTRE for supporting manuals



HONDA XR 190CT

TECHNICAL SPECIFICATIONS



GENERAL INFORMATION:

- country of origin China
- box type carton
- packing condition CBU - semi knock-down
- emission stage 3
- model agricultural
- carrier rear option up to 20kg/front option up to 3kg
- closed hand guard protection bars

ENGINE:

- transmission 5-speed
- starter kick/electric
- engine displacement (cc) 184
- engine power (kW/rpm) 11,1/8.000
- max torque (Nm/rpm) 15,7/5.500
- engine (cylinder) 1
- ignition DC-CDI battery
- system (volt) 12
- engine type OHC air-cooled
- stroke cycle 4
- compression ratio 9.5:1
- suspension, front telescopic fork
- suspension, rear pro-link, swingarm
- fuel tank capacity (L) 13
- fuel economy 52,2 km/L @ 50 km/h
- bore & stroke 61.0 x 63.096mm
- clutch operation mechanical, cable actuated
- clutch lock

BRAKES:

- brakes, front disc
- brakes, rear drum

SEATING:

- seating capacity 1

TYRES:

- tyre front 2.75-21 45M
- tyre rear 90/100-18 M/C 54M
- mudguards front & rear

WEIGHT AND DIMENSIONS:

- curb weight (kgs) 137
- ground clearance (mm) 237
- height (mm) 1.127
- width (mm) 842
- length (mm) 2.103
- seat height (mm) 827
- wheel base (mm) 1.369
- dry weight (kgs) 128
- max carrying capacity (kgs) 95
- color white, red

SHIPPING DIMENSIONS:

- height (box) (mm) 1.200
- width (box) (mm) 520
- length (box) (mm) 1.790
- shipping weight (kgs) 179

WARRANTY:

- 1 year / 12.000 km whichever comes first

Support UN's Sustainable Development Goal 13

Take urgent action to combat climate change and its impacts

4-stroke engine technology is significantly cleaner than a 2-stroke engine due to a cleaner combustion and better fuel economy. Endorsed by UNEP.

13 CLIMATE ACTION



FREE DOWNLOAD CENTRE for supporting manuals

